



Order form
Purchaser

Valid from November 2019
Order no

Vaisala INTERCAP® Humidity and Temperature Probe HMP60

Vaisala INTERCAP® Humidity and Temperature Probe		HMP60																		PRICE
1	Output signals	0...1 V 0...2.5 V 0...5 V 1 ...5V Scaling for 4...20 mA converter (channel 1 only) Modbus RS485	A B C D I M R																	
2	Measured parameter for channel 1	RS485 RH T (-40 ... +60°C) Td (-40 ... +60°C) Tw (-40... +60C) h (-40... 460 kJ/kg)	0 1 2 3 7 8																	
3	Measured parameter for channel 2	RS485 or current interface RH T (-40 ... +60°C) Td (-40 ... +60°C) Tw (-40... +60C) h (-40... 460 kJ/kg)	0 1 2 3 7 8																	
4	Sensor protection	Plastic grid with filter Plastic grid <i>Stainless steel sintered filter</i> Metal Grid with PTFE membrane	A B C F																	
5	Accessories	No accessories Pair of plastic nuts <i>Duct installation kit 215619</i>	0 1 3																	
6	Humidity sensor	Intercap																		
7	Probe cable length	No cable <i>60 °C cable 0.3 m HMP50Z032</i> <i>60 °C cable 3 m HMP50Z30A</i> <i>180 °C FEP cable 3m 226902</i> <i>180°C FEP cable 1.5m 238025</i>	1 2 3 F J																	
8	User guide	No user guide Multilingual quick guide	A B																	
9	Loop power converter	No converter <i>4...20 mA loop power converter</i> Always use single unit package	0 1 2																	
																TOTAL				
																QTY				
																TOTAL VALUE				

Selections in bold are included in the prices of the basic versions.
Selections in italic are available at an extra price.

Example of order code with typical settings:

HMP60	A	1	2	A	0	A	1	B	0
-------	---	---	---	---	---	---	---	---	---